



SPLENDORLUX BILUCIDO

description Two sides Cast Coated boards, high gloss and whiteness. Certify FSC, made with E.C.F. pulp. Available in Premium White colour.

range

size	grain	substance
71x101	LG	210 250 300 380

technical features
standard/instrument
unit of measure

substance	VSA	gloss	Taber stiffness 15°	
ISO 536	ISO 534	ISO 2613	ISO 2493	
g/m ²	cm ³ /g	%	mN	
			long±10%	cross±10%
210 ± 4%	1,00	> 40	65	35
250 ± 5%	1,02	> 40	120	60
300 ± 5%	1,07	> 40	235	125
380 ± 5%	1,08	> 40	340	185

Whiteness - ISO 2470 (R457) - 94% ± 2
Relative Humidity 50% ± 5

ecological features



notes The product is completely biodegradable and recyclable. Special runs available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.



Splendorlux Bilucido is particularly appreciated for converting uses in packaging, portfolios, soft covers, postcards, coordinated graphic materials.

applications

The Splendorlux Bilucido mirror-like surface permits to obtain particularly brilliant printing results with excellent contrast, details and chromatic saturation. Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen printing. When printing in offset it is advisable to use oxidative drying inks and ensure more control at the pH and the conductivity of the fountain solution, in order to keep emulsions at minimum levels. Use of a moderate ink load will result in better control of setting, if necessary use anti set-off spray powder or add ink drier paste.

printing
suggestions

Splendorlux Bilucido gives good results with conventional or U.V. varnishing. Excellent results in plastic laminating. There are no specific recommendations for packaging and converting process. For folding operations prior scoring is advisable.

converting
suggestions