



SYMBOL CARD

description Environmentally-friendly ECF boards (SBS, GZ), certify FSC. Double blade coated on one side with a Satin finish. Available in Premium White colour.

range

size	grain	substance
72x102	LG	210 240 270 300 330



technical features
standard/instrument
unit of measure

substance	thickness	smoothness*	stiffness Taber 15°	
ISO 536	ISO 534	ISO 8791-2	ISO 2493	
g/m ²	µm	ml/min	mNm	
			long±10%	cross±10%
210 ± 4%	250 ± 10	380 ± 20	3,9	2,6
240 ± 5%	285 ± 10	300 ± 20	6	3,8
270 ± 5%	325 ± 10	285 ± 20	9,3	5,5
300 ± 5%	360 ± 10	285 ± 20	11,3	7,3
330 ± 5%	400 ± 10	300 ± 20	15,3	9,5

Whiteness - ISO 2470 (R457) - 104% ± 2
Relative Humidity 50% ± 5
* Uncoated side

ecological features



ELEMENTAL
CHLORINE
FREE
GUARANTEED



notes The product is completely bio-degradable and recyclable. Special runs available upon request.

The company reserves the right to modify the technical characteristics of the products on the basis of market requirements



Symbol Card is excellent for packaging, covers, postcards, brochures, promotional material, CD cases and similar applications.

applications

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen-printing. For offset printing, the characteristics of the coated side are comparable to our Symbol Freelifa Satin, and the uncoated side is designed to provide good printability, also with solid colours.

printing
suggestions

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

converting
suggestions


S Y M B O L™