



SYMBOL MATT PLUS

description Environmentally-friendly ECF papers and boards certify FSC. High content of selected recycled material (minimum quantity guaranteed 25%). Triple blade coated on both sides with a Matt finish.

range	size	grain	substance							
	64x88	LG	100	115	130	150	170	200	250	300
	70x100	LG	100	115	130	150	170	200	250	300

technical features
standard/instrument
unit of measure

substance	VSA	opacity	smoothness	breaking length	
ISO 536	ISO 534	ISO 2471	ISO 8791-2	ISO 1924	
g/m ²	cm ³ /g	%	ml/min	m	
				long±10%	cross±10%
100 ± 3%	0,84	92 ± 2	35 ± 15	4000	3000
115 ± 3%	0,84	93 ± 2	35 ± 15	4000	3000
130 ± 3%	0,84	94 ± 2	30 ± 15	4000	3000
150 ± 3%	0,87	96 ± 2	25 ± 15	4200	3200
170 ± 3%	0,91	–	25 ± 15	4300	3300
200 ± 4%	0,95	–	30 ± 15	-	-
250 ± 5%	1,01	–	30 ± 15	-	-
300 ± 5%	1,02	–	30 ± 15	-	-

Whiteness ISO 2470 (R457) - 104% ± 2
Relative Humidity 50% ± 5

ecological features



notes Given the considerable amount of recycled content within the product it is possible for there to be a slight variation in the shade, from one making to the next. The product is completely biodegradable and recyclable. Special runs available upon request.

The company reserves the right to modify the technical characteristics of the products on the basis of market requirements



Symbol Matt Plus is excellent for publications, packaging, coordinated graphic materials, covers, inserts and de luxe brochures.

[applications](#)

Symbol Matt Plus can be used with all the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen printing.

[printing suggestions](#)

Good results with major processing operations such as: cutting, die cutting, scoring, folding, glueing, varnishing and plastic lamination.

[converting suggestions](#)


S Y M B O LTM